

Clear Image in the Dark

650TV Lines



Premium Resolution WDR Camera

SCB-3001

- High resolution of 650TV lines (Color), 700TV lines (B/W)
- Min. illumination 0.1Lux@F1.2 (Color), 0.01Lux (B/W)
- WDR, VPS, True Day & Night (ICR), Intelligent video, MD
- SSNRIII (3D+2D), Coaxial control (Pelco C),
- RS-485, Dual power & 230V AC

Premium Resolution WDR Camera

SCB-3001




Specifications

	SCB-3001N	SCB-3001P	SCB-3001PH
VIDEO			
Imaging Device	1/3" Double scan CCD		
Total Pixels	1,028(H) x 508(V)	1,028(H) x 596(V)	
Effective Pixels	976(H) x 494(V)	976(H) x 582(V)	
Scanning System	2 : 1 Interlace		
Synchronization	Internal / Line lock / Extern		
Frequency	H : 15.734KHz / V : 59.94Hz	H : 15.625KHz / V : 50Hz	
Horizontal Resolution	Color : 650TV lines, B/W : 700TV lines		
Min. Illumination	Color : 0.1Lux@F1.2 (50IRE), 0.0002Lux (Sens-up, 512x) B/W : 0.01Lux@F1.2 (50IRE), 0.00002Lux (Sens-up, 512x)		
S / N Ratio	52dB (AGC off, Weight on)		
Video Output	CVBS : 1.0 Vp-p / 75Ω composite		
LENS			
Lens Type	Manual / Auto iris (Video / DC)		
Mount Type	C / CS		
OPERATIONAL			
On Screen Display	Multi-language support English, Japanese, Spanish, French, Portuguese, Taiwanese, Korean	Multi-language support English, French, German, Spanish, Italian, Chinese, Russian, Polish, Czech, Romanian, Serbian, Swedish, Danish, Turkish, Portuguese	
Camera Title	Off / On (Displayed 15 characters)		
Day & Night	Auto (ICR) / External / Color / B/W		
Backlight Compensation	Off / User BLC / HLC / SSDR / WDR		
Wide Dynamic Range	128x	160x	
Contrast Enhancement	SSDR		
Digital Noise Reduction	SSNRlll (Off / On)		
Digital Image Stabilization	Off / On		
Motion Detection	Built-in		
Privacy Masking	Off / On (12 programmable zones)		
Sens-up (Frame Integration)	2x ~ 512x		
Gain Control	Off / Low / High		
White Balance	ATW / Outdoor / Indoor / Manual / AWC (1,700K° ~ 11,000K°)		
Electronic Shutter Speed	1/60 ~ 1/120,000sec 1/50 ~ 1/120,000sec		
Digital Zoom	Off / On (1x ~ 16x)		
Reverse	Off / H-Rev / V-Rev / HV-Rev		
Profile	Basic / Day & Night / Backlight / ITS / Indoor / User		
Intelligent Video	Off / On		
VPS	Fixed / Moved / Area / Fence / Tracking / Detection / Counting		
PIP	Off / On		
Alarm	1 Out		
Communication	Coaxial control (SPC-300 compatible), RS-485		
Protocol	Coax : Pelco-C (Coaxitron) RS-485 : Samsung-T/E, Pelco-D/P, Panasonic, Bosch, Honeywell, Vicon		
ENVIRONMENTAL			
Operating Temperature / Humidity	-10°C ~ +50°C (+14°F ~ +122°F) / Less than 90% RH		
ELECTRICAL			
Input Voltage / Current	Dual (24V AC & 12V DC ±10%)		230V AC ±10%
Power Consumption	Max. 4.0W		Max. 4.2W
MECHANICAL			
Color / Material	Black, Silver / Aluminum, Steel		
Dimensions (WxHxD)	66 x 61 x 102mm (2.6" x 2.4" x 4.02")		66 x 61 x 115mm (2.6" x 2.4" x 4.53")
Weight	310g (0.68 lb)		540g (1.19 lb)

Dimensions

Unit : mm (inch)



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

Design and specifications are subject to change without notice.



SAMSUNG TECHWIN CO., LTD.

701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400
Tel : +82-70-7147-8741 ~ 8749, 8752 ~ 8760 Fax : +82-31-8018-3745
www.samsungsecurity.com www.samsungcctv.com

SAMSUNG TECHWIN AMERICA INC.

1480 Charles Willard St, Carson, CA 90746, UNITED STATES
Tel Free : +1-877-213-1222 Fax : +1-310-632-2195
www.samsungcctvusa.com

SAMSUNG TECHWIN EUROPE LTD.

Samsung House, 1000 Hillwood Drive, Hillwood Business Park
Chertsey, Surrey, UNITED KINGDOM KT16 0PS
Tel : +44-1932-45-5300 Fax : +44-1932-45-5325

TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONICS CO., LTD.

No.11 Wei 6 Street, Micro-Electronic Industrial Park
Jingang Road, Tianjin, P.R. CHINA 300385
Tel : +86-22-23887788 Fax : +86-22-23887788

■ DISTRIBUTED BY

