

## **BabyView Flex**

## **SEW-3048W**




## **Key Features**

- 4.3" display monitor with simple UI
- · Easy Installation with a flexible stand
- VOX and ECO Mode
- Long lasting monitor battery (max. 6hrs)
- Long RF communication range
- Two-Way Talk
- Feed Time and Room Temperature display and alert
- 7 pre-programmed lullabies and white noises

## **Package Contents**

- Wireless Camera / Wireless Monitor
- Camera / Monitor Adapters
- Plastic Anchor (2EA) / Screw (2EA)
- Adapter EU Plug (2EA) or UK Plug (2EA)
- User Manual / Warranty Card
- Bracket Accessory



SEW-3048W		
SYSTEM GENERAL	Operating Frequency Range	2400 MHz~2483.5 MHz
	Type of Spread Spectrum TX	FHSS
	Type of Modulation	GFSK
	Number of Camera Support	Up to 4 cameras
	Data Rate	4Mbps
	Transmission range	Up to 274m (line of sight, no obstruction)
	Regulation Compliance	FCC/CE(RoHS)
	Operating Environment	0oC~+40oC / 85% RH / Indoor use only
WIRELESS CAMERA SEB-101CRWP	Image Sensor Type	1/4" Color CMOS Image Sensor
	Effective Pixel	640x480 (VGA)
	Image Compression	MJPEG
	Lens	EFL=3.95mm, F=2.2 (Viewing Angle (D): 55degree)
	Night Vision	5m (16 ft.) in the dark with 8 non-visible IR LEDs
	White Balance	Auto
	Lullabies	4 songs + 3 white noises (Remote On / Off)
	Temperature sensor	Yes (+/-2 degree)
	Power Requirement	DC 5V ±10%
	Power Consumption	2.5Watt (max)
	VOX level detection	Low: 50dBA / High: 65dBA
	Audio	Built in Microphone/ Speaker
WIRELESS MONITOR	Display Information	4.3" 480x272 Color TFT
	Digital Zoom	X1,X2
	Real Time Clock (RTC)	+/- 3sec / day
	Power Requirement	Adapter : DC 5.1V ± 10%, Battery : 3.85V Li-ion
	Power Consumption	4.0Watt (max)
	Audio	Built in Microphone/ Speaker
	Rechargeable Battery	2100mAh Li-ion Polymer
	Battery time duration	Monitor On: 5.5 hours / Audio Only: min. 10 hours